Swivel castor:

# JXPU 2003 6443/B



## Technical data

| | | |
|---|---|---|
| Diameter | | 200 mm |
| Wheel width | | 50 mm |
| Hub length | | 64 mm |
| Height | | 235 mm |
| Offset | | 60 mm |
| Wheel axle diameter | | 20 mm |
| Top plate dimensions | | 135 x 112 mm |
| Top plate hole diameter | | 11 mm |
| Dist. between holes | | 105 x 75,80 mm |
| Brake swivel radius | | 145 mm |
| Load capacity | | 515 kg |
| Weight | | 3.9 kg |

## Technical description

| |
|---|
| Swivel fork of deep drawn stainless steel with wheel brake. |
| Swivelhead with sealed precision ball bearing, grease nippel |
| and O-ring seal. In case of extreme conditions |
| (like frequent jet cleaning) maintenance by relubrication |
| is necessary |

REACH compliant

RoHS compliant

## Wheel

| |
|---|
| Polyamide wheel with polyurethane tyre |
| (Shore A 96) with two deep groove ball bearings |

A company of Colson Group
Colson Rollen GmbH , Industriestraße 8, D-42499 Hückeswagen,
Tel. +49 2192 9368-0, Fax +49 2192 9368-477, info@colson-rollen.com