# Swivel castor with central total brake:

# M28QZ-RF2K125-AS
# (390q 29K125a Z2351ZA)



## Technical data

| | | |
|---|---|---|
| Diameter | | 125 mm |
| Tread width | | 32 mm |
| Height | | 158 mm |
| Offset | | 44 mm |
| Stem size | | 28x100 (41°/52°) mm |
| Load capacity | | 100 kg |
| Weight | | 1100 g |

## Technical description

- sheet steel metal housing
- zinc passivated
- double ball bearing in swivel head
- protected from dust and water ingress by plastic sealing ring
- integrated selection mechanism with total locking brake "q"
- and directional locking brake "r"
- selection mechanism continually greased
- device to permit adjustment of the braking effect
- (without removing the castor or wheel)
- also available with other wheel variants

REACH compliant RoHS compliant

## Wheel

- thermoplastic elastomer tyre (TPE) iron grey RAL 7011 (Shore A 80)
- electrically conductive
- plastic wheel centre and thread guard silver grey RAL7001
- precision ball bearing
- Contact discoloration on unsealed grounds possible!>>

A company of Colson Group
Colson Rollen GmbH , Industriestraße 8, D-42499 Hückeswagen,
Tel. +49 2192 9368-0, Fax +49 2192 9368-477, info@colson-rollen.com