# Swivel castor with central/directional total brake:

# M39RZ-RF2K125-AS
# (391r 29K125a Z985NP)



## Technical data

| | | |
|---|---|---|
| Diameter | | 125 mm |
| Tread width | | 32 mm |
| Height | | 164 mm |
| Offset | | 44 mm |
| Stem size | | 32x50 (30°) mm |
| Load capacity | | 100 kg |

## Technical description

| |
|---|
| sheet steel metal housing |
| zinc passivated |
| presicion ball bearing in swivel head |
| protected from dust and water ingress by plastic sealing ring |
| integrated selection mechanism with total locking brake "q" |
| and directional locking brake "r" |
| selection mechanism continually greased |
| device to permit adjustment of the braking effect |
| (without removing the castor or wheel) |
| also available with other wheel variants |

REACH compliant RoHS compliant

## Wheel

| |
|---|
| thermoplastic elastomer tyre (TPE) iron grey RAL 7011 (Shore A 80) |
| electrically conductive |
| plastic wheel centre and thread guard silver grey RAL7001 |
| precision ball bearing |
| Contact discoloration on unsealed grounds possible!>> |

A company of Colson Group
Colson Rollen GmbH , Industriestraße 8, D-42499 Hückeswagen,
Tel. +49 2192 9368-0, Fax +49 2192 9368-477, info@colson-rollen.com